

Optical Engineering

OpticalEngineering.SPIEDigitalLibrary.org

Errata: Adaptive spatial filtering of daytime sky noise in a satellite quantum key distribution downlink receiver

Mark T Gruneisen
Brett A Sickmiller
Michael B Flanagan
James P Black
Kurt E Stoltenberg
Alexander W Duchane

Errata: Adaptive spatial filtering of daytime sky noise in a satellite quantum key distribution downlink receiver

Mark T Gruneisen,^a Brett A Sickmiller,^b Michael B Flanagan,^b James P Black,^c Kurt E Stoltenberg,^c and Alexander W Duchane^a

^aAir Force Research Laboratory, Directed Energy Directorate, 3550 Aberdeen Avenue S.E., Kirtland Air Force Base, New Mexico 87117-5776, United States

^bLeidos, 2109 Air Park Road S.E., Albuquerque, New Mexico 87106, United States

^cThe Boeing Company, P.O. Box 5670, Albuquerque, New Mexico 87185, United States

[DOI: [10.1117/1.OE.55.5.059801](https://doi.org/10.1117/1.OE.55.5.059801)]

This article [*Opt. Eng.* **55**(2), 026104 (2016)] was originally published on 2 February 2016 with an error in Table 1. In the header row, the unit of measure was mistakenly written as

mmrad. It should have been written as μrad . The corrected table is reprinted below.

The paper was corrected online on 26 April 2016.

Table 1 Turbulence parameters for five elevation angles relative to zenith with 400- and 800-km altitude circular orbit altitudes. Parameters include Fried's coherence length r_0 , the isoplanatic angle θ_0 , Rytov, and the Greenwood frequency f_G . Parameters are shown for $1 \times HV_{5/7}$ and $3 \times HV_{5/7}$ turbulence profiles.

Zenith angle (deg)	400 km altitude				800 km altitude			
	r_0 (cm)	θ_0 (μrad)	Rytov	f_G (Hz)	r_0 (cm)	θ_0 (μrad)	Rytov	f_G (Hz)
$1 \times HV_{5/7}$								
0	8.5	11.82	0.04	250	8.5	11.82	0.04	143
30	7.8	9.47	0.05	275	7.8	9.44	0.05	158
45	6.9	6.86	0.06	315	6.9	6.83	0.07	182
60	5.6	3.96	0.12	403	5.6	3.94	0.12	239
75	3.8	1.41	0.40	697	3.8	1.40	0.40	436
$3 \times HV_{5/7}$								
0	4.4	6.11	0.10	485	4.4	6.11	0.10	277
30	4.0	4.90	0.13	531	4.0	4.88	0.14	305
45	3.6	3.55	0.19	609	3.6	3.53	0.20	353
60	2.9	2.05	0.36	780	2.9	2.04	0.37	462
75	2.0	0.73	1.19	1347	2.0	0.73	2.21	843